



US009499386B2

(12) **United States Patent**
Malinski

(10) **Patent No.:** **US 9,499,386 B2**

(45) **Date of Patent:** **Nov. 22, 2016**

(54) **WINE STORAGE AND DISPENSING APPARATUS**

(71) Applicant: **Jon M. Malinski**, Paradise Valley, AZ (US)

(72) Inventor: **Jon M. Malinski**, Paradise Valley, AZ (US)

(73) Assignee: **Vinocopia, Inc.**, Richfield, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 233 days.

(21) Appl. No.: **14/066,167**

(22) Filed: **Oct. 29, 2013**

(65) **Prior Publication Data**

US 2014/0048559 A1 Feb. 20, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/189,034, filed on Jul. 22, 2011, now Pat. No. 8,596,496.

(51) **Int. Cl.**
B67D 3/00 (2006.01)
F25D 31/00 (2006.01)
F25B 21/02 (2006.01)

(52) **U.S. Cl.**
CPC **B67D 3/0009** (2013.01); **B67D 3/0038** (2013.01); **F25D 31/006** (2013.01); **F25B 21/02** (2013.01); **F25D 2331/801** (2013.01); **F25D 2331/806** (2013.01)

(58) **Field of Classification Search**
CPC . B67D 3/0009; B67D 3/0038; F25D 31/006; F25D 2331/801; F25D 2331/806; F25B 21/02
USPC 222/146.1, 146.6, 185.1, 325, 523, 222/92-107, 129-145.8, 183; 62/3.6, 457.8
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,116,622 A 5/1938 Eisenmenger
2,831,610 A 4/1958 Dennie

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2003-534997 A 11/2003
JP 2007-091334 A 4/2007
KR 2003-0015255 A 2/2003

OTHER PUBLICATIONS

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2011/044966, Mar. 8, 2012, Korean Patent Office, International Searching Authority.

(Continued)


Primary Examiner — Donnell Long

(74) *Attorney, Agent, or Firm* — DuFault Law Firm, P.C.; Dustin R. DuFault

(57) **ABSTRACT**

An apparatus for storing and dispensing wine comprises a housing formed substantially in the shape of a wine barrel. The housing including a circumferential wall, a first closed end and a second open end. A spigot for selectively dispensing wine is supported by and positioned through the first closed end of the housing. A removable insert disposable within the housing through the second open end contains a collapsible bladder of wine. A wine dispensing port is contained within the bladder and insert. With the insert positioned within the housing, the port is positioned proximate the second open end thereof. A conduit in fluid communication with the spigot extends from the first closed end toward the second open end. Upon disposing the insert within the housing, the conduit is connectable to the port wherein the wine can be selectively dispensed from the spigot.

9 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS



3,243,965	A	4/1966	Jepson	
3,476,295	A	11/1969	Henri	
3,696,969	A	10/1972	De Van et al.	
3,760,711	A	9/1973	Webster	
3,933,275	A	1/1976	Metzner et al.	
4,105,139	A	8/1978	Scholle	
4,164,851	A	8/1979	Bryant	
4,304,341	A	12/1981	Shirley	
RE32,354	E	2/1987	Savage	
4,901,886	A	2/1990	Kirschner	
4,921,135	A	5/1990	Pleet	
5,373,872	A	12/1994	Mueller	
5,469,708	A *	11/1995	Harrison	B67D 3/0009 222/146.6
5,634,343	A *	6/1997	Baker, III	B67D 3/0009 222/146.6
6,056,157	A	5/2000	Gehl et al.	
6,250,506	B1	6/2001	Geiger et al.	
6,334,329	B1	1/2002	Weller	
7,178,343	B2	2/2007	Linder	

7,258,252	B2	8/2007	Waters	
7,434,705	B2	10/2008	Evangelista	
8,820,094	B1 *	9/2014	Casher	B67D 3/0054 62/3.2
2002/0162339	A1	11/2002	Harrison et al.	
2004/0144799	A1	7/2004	Danby et al.	
2006/0112717	A1	6/2006	Walton	
2007/0245765	A1	10/2007	Casher	
2007/0284389	A1	12/2007	Jacobs	
2008/0087682	A1	4/2008	Overgaard	
2008/0237260	A1 *	10/2008	Wolek	B67D 3/0009 222/105
2009/0250489	A1	10/2009	Saunders et al.	
2010/0147884	A1	6/2010	Compton et al.	

OTHER PUBLICATIONS

International Preliminary Report on Patentability, PCT/US2011/044966, Jan. 22, 2013.
Office Actions, Responses/Amendments and Notice of Allowance in U.S. Appl. No. 13/189,034.

* cited by examiner






FIG. 3




FIG. 4







FIG. 6








FIG. 11



1

WINE STORAGE AND DISPENSING APPARATUS

CROSS-REFERENCE TO RELATED APPLICATION(S)

The present application claims a benefit of U.S. Provisional Application No. 61/366,877 filed on Jul. 22, 2010, and is a continuation of U.S. Non-Provisional patent application Ser. No. 13/189,034 filed on Jul. 32, 2011, both of which are hereby incorporated herein in their entirety by reference.

BACKGROUND OF THE INVENTION

The present invention generally relates to wine storage devices. More particularly, the present invention relates to an apparatus for storing and dispensing wine from collapsible, reusable containers.

For many years, wine has remained one of the most popular drinks to accompany a meal, and as such, is made available not only at home, but at a vast number of restaurants. It is therefore important for a restaurant to keep in stock ample quantities of wine to meet the demand of its customers. However, as wine has historically been stored within glass 750-mL bottles, not only are there increased shipping costs associated with the use of glass bottles, but stocking a restaurant with such wine requires certain space requirements. Alternatively, certain types of wine have been made available by means of portable fluid containers, for example flexible 3- to 10-liter bladders of wine contained within a cardboard box, sometimes referred to as "wine-in-a-box" or simply "box wine". While such containers cut down on shipping costs, there are still storage considerations to take into account, as well as other inherent setbacks. For instance, as the box itself must be placed within a refrigeration unit to keep the wine chilled, the refrigeration space required for the box must be considered. Further, and regardless if a bottle or portable fluid bladder is used, once opened, the shelf-life of the wine decreases rapidly due to oxidation. While bottles of wine typically have to be consumed within a day or so, "wine-in-a-box" products currently available typically last only about a week. More importantly, though, as wine is considered by many to be a premium product, "wine-in-a-box" does not do well from a marketing standpoint as it has been perceived by the purchasing public to be an inferior product or inferior means of storage as opposed to glass bottles. For this reason alone, many vintners have avoided providing wines in this fashion, preferring instead to stick with glass bottles.

There exist in the art several examples of devices which have attempted to provide a means for storing box wine in an aesthetically pleasing manner. However, limitations exist in such examples as conventional devices have been shown to be quite difficult to change between spent wine bladders and new ones. For example, U.S. Pat. No. 7,434,705 requires that a front end housing containing a dispensing spout be removed before a spent bladder of wine can be replaced with a full bladder of wine. It has been shown in the field that this mechanism is difficult to employ.

Currently, there exists a need in the art to provide an aesthetically pleasing wine dispensing mechanism for use in conjunction with reusable bladders of wine which provides a quick, easy and efficient means of changing between spent and full bladders. There also exists a need in the art to provide a wine dispensing mechanism which assists in

2

preserving unused quantities of wine after opening longer than what is currently available.

BRIEF SUMMARY OF INVENTION

In accordance with the present invention, an apparatus is provided for refrigerating and dispensing pre-packaged wine. The apparatus includes a housing formed substantially in the shape of an aesthetically pleasing miniature wine barrel which holds a removable insert containing between approximately 3 and 10 liters of wine within a collapsible bladder. The housing includes a first circumferential wall, a front face and removable rear panel. A spigot for selectively dispensing the wine is supported by and positioned through the front face. The insert is disposable within the housing through the rear portion with the panel removed. A telescoping conduit in fluid communication with the spigot extends from the front face of the housing to the rear thereof for connection with the insert proximate the rear of the housing. The conduit is positionable between a first retracted position and a second extended position, which facilitates in connecting the bladder thereto.

In replacing a spent bladder, the user removes the rear cover and pulls the insert out slightly such that the connection between the conduit and the insert is easily accessible to the user. This extends the conduit from the first retracted position to the second extended position. The user can then disconnect the spent insert from the conduit, fully remove the spent insert, which can then be replaced by a full insert. The full insert is connected to the conduit and then fully positioned within the housing, which positions the telescoping conduit from the second extended position to the first retracted position. The panel can then be replaced and the apparatus is ready to again dispense wine.

To optionally cool the wine, an electric heat pump extends through an aperture contained within a bottom portion of the housing. The heat pump is capable of expelling thermal energy contained within the housing to keep the wine cool relative to a higher ambient temperature. To facilitate in the cooling of the wine, a thermally conductive shroud is provided which is supported by a thermal conductive block in communication with the heat pump. The shroud is configured to receive and support the insert. Both the shroud and the insert have an angled floor which permits the wine to be gravitationally urged toward the rear of the housing where the conduit fluidly connects to the bladder.

BRIEF DESCRIPTION OF THE DRAWINGS

The following figures are used herein in conjunction with the specification to assist in understanding the invention. The Figures are as follows:

FIG. 1 is a perspective view of a wine storage and dispensing apparatus in accordance with a first embodiment of the present invention.

FIG. 2 is a side-view of the wine storage and dispensing apparatus in accordance with the first embodiment of the present invention.

FIG. 3 is a cross-sectional view of the wine storage and dispensing apparatus as taken along lines A-A in FIG. 2.

FIG. 4 is a cross-sectional view of the wine storage and dispensing apparatus as taken along lines B-B in FIG. 2.

FIG. 5 is a cross-sectional view of the wine storage and dispensing apparatus of the present invention with an insert partially removed.

3

FIG. 6 is a side-view of the wine storage and dispensing apparatus in accordance with a second embodiment of the present invention.

FIG. 7 is a partial cross-sectional side view of a dispensing system in accordance with the present invention.

FIG. 8 is a cross-sectional view of a telescoping conduit in accordance with the present invention.

FIG. 9 is an exploded perspective view of a reusable container in accordance with the present invention.

FIG. 10 is a side profile view of the reusable container in accordance with the present invention.

FIG. 11 is a perspective view of the first and second embodiments of the wine dispensing apparatuses of the present invention supported by a rotatable stand.

DESCRIPTION OF THE INVENTION

A wine storage and dispensing apparatus of the present invention is generally indicated at 100 in FIGS. 1 through 4. The apparatus 100 includes a housing structure 102, preferably an aesthetically shaped miniature wooden wine barrel, for placement on or near a bar in areas where wine would normally be dispensed. However, it should be noted that alternative shapes for the housing structure are well within the scope of the present invention, including non-exhaustive examples of semi-circular barrels with flat bottoms, rectangular boxes or the like. The wine barrel 102 includes a front face 104 which supports a spout or spigot 106 for selectively dispensing wine. A removable back panel 108 attaches to the wine barrel 102 by means of a latching mechanism 110. The specific latching mechanism 110 employed is not critical in practicing the invention, and those skilled in the art will recognize that other mechanisms than those illustrated will suffice.

The apparatus 100 further includes an optional thermoelectric heat pump 112 for cooling wine contained within the barrel 102. The thermoelectric heat pump 112 for use with the present invention includes a solid-state active heat pump which transfers heat from one side 114 of the device to the other side 116 against a temperature gradient with the consumption of electrical energy. A heat sink 117 effectuates dissipation of heat into the air. As best illustrated in FIGS. 3 through 5, the thermoelectric heat pump 112 is positionable through an aperture 118 contained in an under portion of the housing. As it is contemplated that in most situations the ambient temperature of the room or restaurant where the apparatus 100 will be dispensing wine will be greater than optimal wine dispensing temperatures of between 45 and 65 degrees Fahrenheit, the heating portion 116 of the thermoelectric cooler seats outside of the barrel 102, enabling any generated heat to dissipate into the outside air. Attached to the cooling side 114 of the heat pump is a thermally conductive block 120, preferably constructed of a metallic material such as aluminum. However, any material having a thermal conductivity greater than about 100 watts per meter Kelvin ($W/(m \cdot K)$) is well within the scope of the present invention. The thermoelectric heat pump 112 further includes a control unit and electric transformer (not shown) for activating and controlling the temperature of the block 120 and shroud 122, which in turn controls the temperature of the wine. Exemplary thermoelectric heat pumps 112 for use with the present invention include those as made available by Pacific Supercool, Ltd. of Bangkok, Thailand or SOS Prescott of Prescott, Wis. However, one skilled in the art will recognize that the use of similar thermoelectric heat pumps by other manufacturers are well within the scope of the present invention.

4

To increase the efficiency and the consistency of the manner in which heat is conducted out of the wine barrel 102, and to provide for a more consistent temperature therein, the metallic shroud 122 is provided. The shroud 122 seats upon and engages the conductive block 120. The metallic shroud includes a base plate 124 attached to the conductive block 120, as well as a semi-circular wall 126 extending along longitudinal edges of the base plate 124. Insulation 125 may be provided between the shroud 122 and the inner wall 128 of the barrel. Further, thermal electric compound 127, such as thermal grease, may be optionally included between the conductive block 120 and the inner wall 128, as is illustrated in FIG. 5. The shroud 122 is designed to support a removable plastic insert 130 containing a collapsible bladder 132 of wine.

As mentioned, use of the thermoelectric heat pump 112 is optional and the present invention can be practiced without such a device, as is illustrated in alternative embodiment 200 in FIG. 6. However, for purposes of this description, similar parts from apparatus 100 and alternative apparatus 200 will be given similar references, and any differences between the two embodiments will be explicitly stated. As such, unless otherwise noted, description of one is meant to include description of the other for similar parts and operation.

To transfer the wine contained within the bladder 132 positioned within the insert 130, a liquid transfer mechanism 134 is provided. As illustrated in FIG. 7, the liquid transfer mechanism 134 includes the spigot 106 in fluid communication with a telescoping conduit 136, which in turn fluidly connects to a quick connector 138. The spigot 106, as made available by Artisan Barrels of Oakland, Calif., threadably attaches to a first segment 140 of the telescoping conduit 136, wherein a seal is formed by means of a washer 141. As illustrated in FIG. 8, the telescoping conduit includes the first segment 140 into which slidably disposes a second segment 142, as denoted by arrow 143. The second segment 142 is therefore of a lesser diameter than the first segment 140. Both the first segment 140 and the second segment 142 are preferably constructed of a rigid material, for example stainless steel. The second segment 142 is slidably positionable relative to the first segment 140 to increase or decrease the overall length of the telescoping conduit 136, the importance of which will become apparent shortly. In order to prevent leakage of liquid when passing therethrough, and to prevent the intrusion of any unwanted material therein, the second segment 142 includes a flange 144 extending circumferentially and slidably engaging an inner surface 146 of the first segment 140. Additionally, an O-ring 148 is positionable within a groove contained in the first segment 140. The O-ring 148 abuts against an outer surface 150 of the second segment 142, which further enhances the seal between the first segment 140 and the second segment 142.

The quick connect 138 is preferably a VITOP® BAG-IN-BOX® quick connect as made available by the Smurfit Kappa Group of Eperry, France. The quick connect 138 includes a male and female connector, 152 and 154 respectively. The female connector 154 connects to the second segment 142 by means of a flexible length of tubing 156. The tubing 156 is preferably anti-microbial to prevent the intrusion of micro-organisms into the wine which can lead to the spoilage thereof. The male connector 152 attaches to the bladder 132 and seats within an aperture 158 contained within the insert 130. The telescoping conduit 136, as well as the connecting tube 156 and a portion of the quick connect 138, is disposable within a circular channel 160 contained within the conducting block 120 as illustrated in FIGS. 3 and 4.

Referring now to FIG. 9, the removable insert 130 is constructed from plastic and includes a substantially flat rectangular floor 162 containing the circular aperture 158 for receiving the male connector 152. A semi-circular wall 164 extends from opposing longitudinal sides of the bottom 162. The semi-circular wall 164 and bottom 162 are joined on a first end by an end-wall 166. A removable cap 168 is securable to a second end portion of the bottom 162 and semi-circular wall 164. The insert 130 houses the collapsible bladder 132 which is fillable with liquid, which in this case includes wine. The male connector 152 fluidly communicates with the bladder 132 and provides the wine to the liquid transfer mechanism 134 when connected thereto. Both the end wall 166 and removable cap 168 include a semi-circular design with a bottom flat portion such that the insert conforms to the shape of the barrel 102 and is disposable within the shroud 122. In order to facilitate gravitational draining of the bladder contents during use, the cap 168 includes a larger circular radius x than a circular radius of the end-wall y , giving the semi-circular wall 164 a frusto-conical configuration. With the end-wall 166 and cap 168 being positioned substantially parallel to one another, the floor 162 therefore is positioned at a declining angle from the end-wall 166 as the floor 162 proceeds towards the cap 168 relative to the top of the semi-circular wall 164, as illustrated in FIG. 10. As the shroud 122 is configured to receive the insert 130, it should be understood that the base plate 124 also includes a corresponding declination.

As is known in the art, the bladder 132 may be constructed of a flexible material such that it may collapse upon itself when the contents therein are drained. Such materials can include metallic sheeting or plastic formed to provide a hermetically sealed interior. To fill the bladder 132, all air is first evacuated after which the wine is introduced therein. Upon being filled, the bladder 132 is injected with an overpressure of an inert gas, such as Argon, to prevent oxygenation of the wine and thereby extend shelf life. Further, by filling the bladder 132 with an inert gas, it has been discovered that the wine can remain unspoiled after opening for a much longer time than is observed within conventional wine-in-a-box methods. Instead of less than two weeks, which is typical for a conventional device, the wine dispensing apparatus 100 of the present invention can prevent oxygenation and spoiling of the wine after opening for up to eight weeks.

It is intended that either the vintner or the wine wholesaler fills the bladders 132 with wine, along with the overpressure of inert gas prior to sealing the bladder 132 within the insert 130. The insert 130 thereby provides a protecting structure to prevent the bladder 132 from being punctured during transit or use. The vintner or wholesaler then ships the insert, or a plurality of inserts, directly to the restaurant when they can be stored until needed for dispensing.

In operation, the apparatus 100 or 200 containing an insert with wine contained therein is positioned within a restaurant, home or other suitable place where it is convenient to dispense the wine into individual glasses when so desired. Upon depleting the contents of a bladder 132, whereby the wine insert needs to be replenished, the back cover 108 of the housing 102 is removed. As illustrated in FIG. 6, the user pulls the insert 130 partially from the shroud 122, causing the second segment 142 of the telescoping conduit to withdraw from the first segment 140 and allowing the user access to the quick connector 138. The user then removes the male connector 152 from the female connector 154, whereby the insert 130 is fully removable from the shroud 122 and the housing 102. A new insert containing a full bladder of wine

is then partially disposed within the barrel and the shroud. The male connector 152, which comes already connected to the bladder 132, is then attached to the female connector 154 and the insert 130 is pushed fully within the shroud 122 with the telescoping conduit 136 decreasing in overall length. The back cover 108 is replaced and the apparatus 100 or 200 is again ready to dispense the wine through the spigot 106. Upon activating the thermoelectric heat pump 112, the wine within the insert 130 is storable at a constant temperature for up to 8 weeks.

Another advantage of the present invention is that it permits ease of operation in an aesthetically pleasing manner without undue hardship in exchanging inserts. As illustrated in FIG. 11, apparatus 100, apparatus 200, or both, can be positioned on a rotatable stand 180, which in turn can be set up on a table, bar top or other suitable location. The stand may include a rotatable base 182, which when the wine in the bladder goes empty, can simply be rotated around to give a person access to the rear of the housing without having to lift and move the housing itself. A depleted insert can be exchanged with a full insert in the manner as previously described, whereafter the stand can be rotated back to its desired position.

Although the present invention has been described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

The invention claimed is:

1. An apparatus for dispensing pre-packaged wine, the wine containable within an insert, the apparatus comprising:
 - a housing configured substantially in the shape of a wine barrel, the housing including:
 - a circumferential wall;
 - a front face fixedly connected to a first end of the wall; and
 - a removable back panel attachable to an opposing second end of the wall;
 - a latching mechanism to removably secure the back panel to the opposing second end of the wall;
 - a floor member disposed within the housing extending from the front face toward the back panel;
 - a spigot for selectively dispensing wine, the spigot supported by and positioned through the front face of the housing below the floor member; and
 - a conduit positioned within the housing below the floor member, the conduit connected to the spigot and extending toward the second end of the wall, wherein the insert containing the pre-packaged wine is disposable within the housing through the second end of the wall with the back panel removed, the insert supportable by the floor, wherein the conduit is fluidly connectable to the insert proximate the second end of the wall.
2. The apparatus of claim 1 further comprising:
 - an electric heat pump extending through an aperture contained within the circumferential wall of the housing, the heat pump for expelling thermal energy out of the housing; and
 - a thermally conductive block engaged to the heat pump, wherein the conduit disposes through an aperture contained within the thermally conductive block.
3. The apparatus of claim 2 wherein the floor member is configured to form a shroud for receiving the insert, the shroud being thermally insulated.
4. An apparatus for storing and dispensing wine contained within a reusable insert, the insert having a first end and an

7

opposing second end, the insert containing a port positioned proximate the second end, the apparatus comprising:

- a circumferential wall having a first end and a second end; a front face affixed to the first end of the circumferential wall;
- a rectangular platform disposed within the circumferential wall, the platform extending lengthwise along the circumferential wall from the front face toward the second end, the platform for supporting the insert, the insert fully disposable within the circumferential wall by positioning the first end of the insert through the second end of the circumferential wall, the port accessible through the second end of the circumferential wall with the insert fully disposed within the circumferential wall;
- a spigot for selectively dispensing the wine contained within the insert, the spigot supported by and positioned through the front face below the rectangular platform;
- a conduit disposed within the circumferential wall beneath the platform, the conduit having a first end attachable to the spigot and a second end connectable to the port of the insert;
- a removable panel connectable to the second end of the circumferential wall; and
- a latching means for securing the panel to the second end of the circumferential wall, wherein disposing the insert within the housing through the second open end, the panel is connectable to the second end of the circumferential wall.

5. The system of claim 4 and further comprising a refrigerating mechanism to chill wine contained within the insert, the refrigerating mechanism comprising:

- a thermally conductive block connected to the platform, the block containing an aperture therethrough for receiving the conduit;
- a thermal shroud supported by the platform, the shroud having a circumferential wall configured to receive and support the insert; and
- a heat pump extending from the block through an aperture contained within a bottom portion of the housing.

8

6. The system of claim 5 and further comprising insulation positioned between an outer surface of the shroud and an inner surface of the housing.

7. An apparatus for dispensing pre-packaged wine, the wine containable within an insert, the apparatus comprising:

- a housing configured substantially in the shape of a wine barrel, the housing including:
 - a circumferential wall;
 - a front face fixedly connected to a first end the wall; and
 - a removable back panel attachable to an opposing second end of the wall;
- a latching mechanism to secure the back panel to the opposing second end of the wall;
- a shroud member disposed within the housing extending from the front face toward the back panel;
- a spigot for selectively dispensing wine, the spigot supported by and positioned through the front face of the housing below the shroud member; and
- a conduit positioned within the housing below the shroud member, the conduit connected to the spigot and extending toward the second end of the wall, wherein the insert containing the pre-packaged wine is disposable within the housing through the second end of the wall with the back panel removed, the insert supportable by the shroud member, wherein the conduit is fluidly connectable to the insert proximate the second end of the wall.

8. The apparatus of claim 7 further comprising:

- an electric heat pump extending through an aperture contained within the circumferential wall of the housing, the heat pump for expelling thermal energy out of the housing; and
- a thermally conductive block engaged to the heat pump, the thermally conductive block containing a surface defining an aperture positioned therethrough, wherein the conduit disposes through the aperture of the thermally conductive block.

9. The apparatus of claim 7 wherein the shroud member is thermally insulated.

* * * * *